



Dehumidification



Super silent



Timer



Total auto-protection

# PORTABLE

## AIR CONDITIONER

Model	CH-PDH12AC1	CH-PDH14AC1
Btu/Hour	12000	13500
Cooling Area (Sq Ft)	500-550	550-700



Bedrooms | Living Rooms | Dining Rooms | Home Offices | Sunrooms | Basements | Computer / Server Rooms

[www.cooperandhunter.us](http://www.cooperandhunter.us)

# PORTABLE

# ALL SEASON COMFORT CONTROL

## FEATURES

- Auto Restart Function;
- Auto Swing;
- Omni directional Caster;
- Flexible Installation;
- Self evaporative System;
- Convenient handle;
- Refrigerant Leakage Detect;
- Bucketfree design;
- Quick room cooling;
- Doesn't create negative pressure inside rooms;
- Sleep Mode;
- Timer;
- Double air deflector and air distribution more uniform;
- Stylish smooth curve design;
- Small and exquisite;
- Self-diagnosis and Auto-protection;
- Filter Clean Reminder;
- Sleep mode;
- Available in Single or Dual Hose.



Dehumidification



Super silent



Timer



Total auto-protection



Model			CH-PDH12AC1	CH-PDH14AC1
Power supply		Ph-V-Hz	1PH, 115V~, 60Hz	1PH, 115V~, 60Hz
Cooling	Capacity	Btu/h	12000	13500
	Input	W	1350	1520
	Current	A	11,7	11,8
	EER	W/W	2.6	2.6
		Btu/W.h	8.9	8.9
Compressor	Type		ROTARY	ROTARY
	Rated current(RLA)	A	7.52	7.52
	Locked rotor Amp(LRA)	A	48.8	48.8
MOCP		A	15	15
Indoor side air flow (Hi)		CFM	218	224
Indoor side noise level(Hi)		dB(A)	57	57,5
Outdoor side noise level (Hi)		dB(A)	60,5	61
Refrigerant type		ozs	R410A/16.23	R410A/21.88
Control type			Remote Control	Remote Control
Operation temp (room temp.)		°F	62°F ~ 95°F /-	62°F ~ 95°F /-
Application area		ft <sup>2</sup>	500-550	550-700
Dimension (W*D*H)		in	17.4x17.0x30.5	17.4x17.0x30.5
Packing (W*D*H)		in	21.1x20.2x34.5	21.1x20.2x34.5
Net/Gross weight		lb	71.7/82.5	73.9/84.7



Preserving resources remains our top priority, so we've printed this piece on recycled materials.



For more information, visit | [cooperandhunter.us](http://cooperandhunter.us)